

PRODUCT INFORMATION PACKET

Model No: 5KCR49WN6075
Catalog No: C178
3/4, 1200, DP, 56, 1/60/115/230
Open Drip Proof (ODP)



Regal and Marathon are trademarks of Regal Beloit Corporation or one of its affiliated companies.
©2019 Regal Beloit Corporation, All Rights Reserved. MC017097E





Nameplate Specifications

Output HP	3/4 HP	Output KW	0.56 kW
Frequency	60 Hz	Voltage	115/230 V
Current	12.6 A	Speed	1140 RPM
Service Factor	1.15	Phase	1
Efficiency	0 %	Duty	Continuous
Insulation Class	B	Design Code	L
KVA Code	K	Frame	56
Enclosure	Drip Proof	Overload Protector	N/R
Ambient Temperature	40 °C	Drive End Bearing Size	6203
Opp Drive End Bearing Size	6203	UL	Recognized
CSA	Yes	CE	N

Technical Specifications

Electrical Type	Capacitor Start Capacitor Run	Starting Method	SM
Poles	6	Rotation	Counterclockwise/Clockwise
Mounting	Rigid Base	Motor Orientation	ANY
Drive End Bearing	BALL	Opp Drive End Bearing	BALL
Frame Material	Rolled Steel	Overall Length	13.96 in
Frame Length	9.63 in	Shaft Extension	.625 X 1.88 - KEY .188 X .188 in
Outline Drawing	52A109641P1	Connection Diagram	52A105381AF

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created: 09/23/2019

